SPECIFICATIONS FOR LINE ITEM 2 COMPRESSOR

HITACHI- SRM Semi-Hermetic Screw Compressor

70 hp Compressor
MODEL 6002 SC-H

50 HZ OPERATION	KCAL/H	170,000
60 HZ OPERATION	KCAL/H	204,500
50 HZ OPERATION	Btu/h	674,500
60 HZ OPERATION	Btu/h	811,500
MOTOR INPUT		
50 HZ OPERATION	kW	49.5
60 HZ OPERATION	kW	59.5
OVERALL DIMENSIONS		
HEIGHT	Mm	536
	(ft-in)	(1-9)
WIDTH	Mm	465
	(ft-in)	(1-6-1/4)
LENGTH	Mm	1,220
	(ft-in)	(4-0-0)
NET WEIGHT	Kg	450
	(lbs)	(995)
SHIPPING WEIGHT	Kg	508
	(lbs)	(1,120)
DISPLACEMENT		
50 HZ OPERATION	m/h	208.8
	(cfm)	(122.8)
60 HZ OPERATION	m/h	251.5
	(cfm)	(148.0)
PIPING CONNECTION		
SUCTION PIPING O.D.	Mm	60.5
I.D.	(in)	(2)
DISCHARGE PIPING O.D.	Mm	48.6
I.D.	(in)	(1-1/2)
ELECTRICAL REQUIREMENTS:	480 VOLTS 3PHASE 60HZ	

MUST INCLUDE:
1. NEW MOTOR PROTECTORS
2. CRANKCASE HEATERS
3. OIL CHANGE KITS
4. OIL SAMPLE BOTTLES
5. SIX MONTH WARRANTY

SPECIFICATIONS FOR LINE ITEM 1 COMPRESSOR

HITACHI- SRM Semi-Hermetic Screw Compressor

60 hp Compressor
MODEL 5002 SC-H

50 HZ OPERATION	KCAL/H	138,000
60 HZ OPERATION	KCAL/H	166,000
50 HZ OPERATION	Btu/h	547,500
60 HZ OPERATION	Btu/h	658,500
MOTOR INPUT		
50 HZ OPERATION	kW	40.0
60 HZ OPERATION	kW	48.0
OVERALL DIMENSIONS		
HEIGHT	Mm	536
	(ft-in)	(1-9)
WIDTH	Mm	465
	(ft-in)	(1-6-1/4)
LENGTH	Mm	1,190
	(ft-in)	(3-10-3/4)
NET WEIGHT	Kg	430
	(lbs)	(950)
SHIPPING WEIGHT	Kg	476
	(lbs)	(1,050)
DISPLACEMENT		
50 HZ OPERATION	m/h	169.5
	(cfm)	(99.8)
60 HZ OPERATION	m/h	204.2
	(cfm)	(120.2)
PIPING CONNECTION		
SUCTION PIPING O.D.	Mm	60.5
I.D.	(in)	(2)
DISCHARGE PIPING O.D.	Mm	48.6
I.D.	(in)	(1-1/2)
ELECTRICALREQUIREMENTS:	480 VOLTS 3PHASE 60HZ	

MUST INCLUDE:
1. NEW MOTOR PROTECTORS
2. CRANKCASE HEATERS
3. OIL CHANGE KITS
4. OIL SAMPLE BOTTLES
5. SIX MONTH WARRANTY